

### Blasting machines VSV Schaffler

#### Capacitor-blasting machines - not firedamp safe

| No.  | Type       | Igniter      | Circuit | Maximum allowable resistance in Ohm | Weight kg |
|--|------------|--------------|---------|-------------------------------------|-----------|
| 2601   | 815        | 10 U         | S       | 55                                  | 1,9       |
| 2602   | 818        | 50 U         | S       | 195                                 | 2,0       |
| <b><u>Blasting Machine for U and HU detonators</u></b> |            |              |         |                                     |           |
| 2603   | 861        | 160 U        | S (S/P) | 580                                 |           |
|  |            | 40 HU        | S       | 25                                  | 9,0       |
| 2606   | 922/3000   | 350 U        | S (S/P) | 1260                                |           |
|  |            | 90 HU        | S       | 50                                  | 16,0      |
| 2607   | 932/3000   | 350 U        | S (S/P) | 1325                                |           |
|  |            | 160 HU       | S       | 85                                  | 21,0      |
| 2608   | 944/3      | 350 U/700 U  | S (S/P) | 1250                                |           |
|  |            | 150 HU/300HU | S       | 80                                  | 30,0      |
| 2609   | 888/2500/2 | 320 U        | S (S/P) | 1140                                |           |
|  |            | 140 HU       | S       | 75                                  | 60,0      |

#### Capacitor-blasting machines - firedamp safe

|      |        |       |         |     |     |
|------|--------|-------|---------|-----|-----|
| 2610 | 804    | 10 U  | S       | 55  | 1,8 |
| 2611 | 806 S  | 25 U  | S       | 110 | 2,6 |
| 2612 | 808 T  | 50 U  | S       | 195 | 2,6 |
| 2613 | 844 T  | 100 U | S (S/P) | 370 | 6,7 |
| 2614 | 844 TS | 150 U | S (S/P) | 545 | 7,0 |

*S = Series, P = parallel, S/P = series-parallel*

#### Tester

2620 Solus: 804, 806 S, 808 T, 844 T

2621 Solus: 815, 818

2622 Solus: 861

2623 Solus: 922/3000

2624 Solus: 932/3000

2625 Solus: 944/3